

### LANDING NIPPLE PROFILE CHART

TUBING O.D.		TOP No-Go LANDING IPPLES				SELECTIVE LANDING NIPPLES				BOTTOM NO-GO TYPE LANDING NIPPLES												
		Baker-Style "GF"				Otis-Style "GX"				Baker-Style "GR"					Otis-Style "GXN"							
		SEAL BORE		MIN O.D.* Box by Pin Threads		SEAL BORE		NIPPLE O.D. Pin by Pin Threads.		SEAL BORE		NO-GO I.D.		MIN O.D.* Box by Pin Threads		SEAL BORE		NO-GO I.D.		NIPPLE O.D. Pin by Pin Threads.		
in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	
1.660	42.15	1.187	30.15	1.875	47.63					1.187	30.15	1.135	28.83	1.875	47.63							
		1.250	31.75			1.250	31.75	1.890	48.01	1.250	31.75	1.198	30.43			1.250	31.75	1.135	28.83	1.890	48.01	
1.900	48.26	1.437	36.50	2.109	53.57					1.437	36.50	1.385	35.18	2.109	53.57							
		1.500	38.10			1.500	38.10	2.130	54.10	1.500	38.10	1.447	36.75			1.500	38.10	1.448	36.78	2.130	54.10	
2.063	53.37	1.562	39.67	2.250	57.15					1.562	39.67	1.510	38.35	2.250	57.15							
		1.625	41.28			1.625	41.28	2.340	59.44	1.625	41.28	1.572	39.93			1.625	41.28	1.536	39.01	2.340	59.44	
2.375	60.33	1.781	45.24	2.560	65.02					1.781	45.24	1.728	43.89	2.560	65.02							
		1.812	46.02							1.812	46.02	1.760	44.70									
		1.875	47.63			1.875	47.63	2.710	68.83	1.875	47.63	1.822	46.28			1.875	47.63	1.791	45.49	2.710	68.83	
2.875	73.02	2.062	52.37	3.109	78.97					2.062	52.37	1.965	49.91	3.109	78.97							
		2.125	53.98							2.125	53.98	2.035	51.69									
		2.188	55.58																			
		2.250	57.15																			
		2.312	58.72			2.312	58.72	3.230	82.04	2.312	58.72	2.259	57.38			2.312	58.72	2.205	56.01	3.230	82.04	
3.500	88.90	2.562	65.07	3.687	93.65					2.562	65.07	2.442	62.03	3.687	93.65							
		2.750	69.85							2.750	69.85	2.697	68.50			2.750	69.85	2.635	66.93	4.250	107.95	
		2.812	71.42			2.812	71.42	4.250	107.95	2.812	71.42	2.759	70.08			2.812	71.42	2.666	67.72			
4.500	114.30	3.688	93.68	5.200	132.08					3.688	93.68	3.625	92.08	5.200	132.08							
		3.750	95.25							3.750	95.25	3.700	93.98									
		3.812	96.82			3.812	96.82	4.940	125.48	3.812	96.82	3.759	95.48			3.812	96.82	3.725	94.62	4.940	125.48	

\* NIPPLE O.D. IS NORMALLY COUPLING O.D. NIPPLE CANNOT BE SMALLER THAN THE DIMENSION SHOWN.

**Otis®** is a registered trademark of Halliburton Energy Services Inc.

**Baker®** is a registered trademark of Baker Hughes Inc.