



COMMON LANDING NIPPLE PROFILE CHART

TUBING O.D.		TOP No-Go LANDING NIPPLES				SELECTIVE LANDING NIPPLES				BOTTOM No-Go LANDING NIPPLES											
		Giant Oil Tools Ltd., "GF"				Giant Oil Tools Ltd., "GX"				Giant Oil Tools Ltd., "GR"					Giant Oil Tools Ltd., "GXN"						
		SEAL BORE		MIN O.D.* Box by Pin Threads		SEAL BORE		NIPPLE O.D. Pin by Pin Threads.		SEAL BORE		NO-GO I.D.		MIN O.D.* Box by Pin Threads		SEAL BORE		NO-GO I.D.		NIPPLE O.D. Pin by Pin Threads.	
in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.		
1.660	42.15	1.187	30.15	2.200	55.88	1.250	31.75	2.200	55.88	1.187	30.15	1.135	28.83	2.200	55.88	1.250	31.75	1.135	28.83	2.200	55.88
		1.250	31.75							1.198	30.43	1.250	31.75			1.447	36.75				
1.900	48.26	1.437	36.50	2.500	63.50	1.500	38.10	2.500	63.50	1.437	36.50	1.385	35.18	2.500	63.50	1.500	38.10	1.448	36.78	2.500	63.50
		1.500	38.10							1.510	38.35	1.500	38.10			1.448	36.78				
2.063	53.37	1.562	39.67	2.325	59.06	1.625	41.28	2.325	59.06	1.562	39.67	1.510	38.35	2.325	59.06	1.625	41.28	1.536	39.01	2.325	59.06
		1.625	41.28							1.572	39.93	1.625	41.28			1.536	39.01				
2.375	60.33	1.781	45.24	3.063	77.80	1.875	47.63	2.710	68.83	1.781	45.24	1.728	43.89	3.063	77.80	1.875	47.63	1.791	45.49	2.710	68.83
		1.812	46.02							1.760	44.70	1.812	46.02			1.760	44.70				
2.875	73.02	2.062	52.37	3.668	93.17	2.312	58.72	3.230	82.04	2.062	52.37	1.965	49.91	3.668	93.17	2.312	58.72	2.205	56.01	3.668	93.17
		2.125	53.98							2.125	53.98	2.035	51.69			2.125	53.98				
		2.188	55.58							2.250	57.15	2.250	57.15			2.197	55.80	2.250	57.15		
		2.250	57.15							2.312	58.72	2.312	58.72			2.259	57.38	2.312	58.72		
		2.312	58.72							2.562	65.07	2.562	65.07			2.442	62.03	2.562	65.07		
		2.562	65.07							2.750	69.85	2.750	69.85			2.697	68.50	2.750	69.85		
3.500	88.90	2.812	71.42	4.500	114.30	2.750	69.85	4.250	107.95	2.812	71.42	2.759	70.08	4.500	114.30	2.750	69.85	2.635	66.93	4.500	114.30
		2.812	71.42			2.812	71.42			2.666	67.72	2.812	71.42			2.666	67.72				
4.500	114.30	3.688	93.68	5.563	141.30	3.750	95.25	4.940	125.48	3.688	93.68	3.625	92.08	5.563	141.30	3.750	95.25	3.700	93.98	5.563	141.30
		3.750	95.25			3.812	96.82			3.812	96.82	3.759	95.48			3.812	96.82	3.725	94.62		

NOTE: NIPPLE O.D. IS NORMALLY API COUPLING O.D. NIPPLE O.D.'s will change for Premium end connections.
 *GF" Landing Nipples are comparable to Baker Hughes F" Nipple Profile.
 *GR" Landing Nipples are comparable to Baker Hughes R" Nipple Profile.
 *GX" Landing Nipples are comparable to Halliburton's X" Nipple Profile.
 *GXN" Landing Nipples are comparable to Halliburton's XN" Nipple Profile.

TUBING O.D.		SELECTIVE LANDING NIPPLES				BOTTOM No-Go LANDING NIPPLES					
		Giant Oil Tools Ltd., "GOR"				Giant Oil Tools Ltd., "GORN"					
		SEAL BORE		NIPPLE O.D.		SEAL BORE		NO-GO I.D.		NIPPLE O.D.	
in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.
2.375	60.33	1.710	43.43	3.063	77.80	1.710	43.43	1.560	39.62	3.063	77.80
		1.781	45.24			1.781	45.24	1.640	41.66		
		1.875	47.63			1.875	47.63	1.716	43.59		
2.875	73.03	2.000	50.80	3.668	93.17	2.000	50.80	1.881	47.78	3.668	93.17
		2.125	53.98			2.125	53.98	1.937	49.20		
		2.188	55.58			2.188	55.58	2.010	51.05		
		2.313	58.75			2.313	58.75	2.131	54.13		
3.500	88.90	2.562	65.07	4.500	114.30	2.562	65.07	2.329	59.16	4.500	114.30
		2.750	69.85			*2.750	69.85	2.620	66.55		
		2.813	71.45								
4.500	114.30	3.437	87.30	5.563	141.30	3.437	87.30	3.260	82.80	5.563	141.30
		3.688	93.68			3.688	93.68	3.456	87.78		
		3.750	95.25			*3.750	95.25	3.518	89.36		
		3.813	96.85			3.813	96.85	3.720	94.49		

*Giant Oil Tools Lock Mandrels must be used in these GORN Landing Nipples.
 *GOR" Landing Nipples are comparable to Halliburton's R" Nipple Profile.
 *GORN" Landing Nipples are comparable to Halliburton's RN" Nipple Profile.