



PRODUCT OVERVIEW

Giant Oil Tools Model G-WR Retrievable Bridge Plug is a wireline set, retrievable bridge plug utilized for zonal isolation, wellbore suspension, surface repairs or any application where wellbore pressure containment is required.

The G-WR Retrievable Bridge Plug features a double acting slip that securely anchors the plug against differential pressure above and below the tool. The 3 element design ensures proper sealing with high pressure and high temperature operations.

The G-WR Retrievable Bridge Plug uses an equalizing valve to allow for pressure differential to be equalized prior to releasing the plug. This allows for easy retrieval when the plug is run on endless tubing.

The G-WR Retrievable Bridge Plug is run and set on wireline utilizing an E4 style pressure setting tool (or equivalent tubing conveyed hydraulic setting tool). It is retrieved on tubing with the G-WR Retrieving Tool.

FEATURES & BENEFITS

- Wireline or Hydraulic Set
- May be run and retrieved on wireline, coil or conventional tubing
- May be lubricated into the wellbore under pressure
- Ideal for rigless operations
- Three element design for reliable high pressure, high temperature operation
- Proven equalizing valve system
- One-piece, double acting slips hold pressure securely from above or below





SPECIFICATIONS

G-WR Wireline Set Retrievable Bridge Plug								
Product Number	Casing Size		Weight		ID		Gauge Ring O.D.	
	in.	mm	lbs/ft	kg/m	in.	mm	in.	mm
G10-049-0440	4-1/2"	114.3	15.1	22.62	3.826	97.18	3.695	93.9
G10-049-0450	4-1/2"	114.3	9.5 - 13.5	14.13 - 20.09	3.920 - 4.090	99.57 - 103.99	3.750	95.3
G10-049-0500	5"	127	15.0 - 18.0	22.32 - 26.78	4.276 - 4.408	108.61 - 111.96	4.125	104.8
G10-049-0510	5"	127	11.5 - 13.0	17.11 - 19.34	4.494 - 4.560	114.15 - 115.82	4.250	108.0
G10-049-0540	5-1/2"	139.7	26.0	38.68	4.548	115.52	4.400	111.8
G10-049-0550	5-1/2"	139.7	17.0 - 23.0	25.29 - 34.23	4.670 - 4.892	118.62 - 124.26	4.500	114.3
G10-049-0560	5-1/2"	139.7	15.5 - 17.0	23.06 - 25.29	4.892 - 4.950	124.26 - 125.73	4.641	117.9
G10-049-0690	7"	177.8	32.0 - 35.0	47.6 - 52.1	6.004 - 6.094	152.5 - 154.8	5.812	147.6
G10-049-0700	7"	177.8	26.0 - 32.0	38.68 - 47.61	6.094 - 6.276	154.79 - 159.41	5.875	149.2
G10-049-0710	7"	177.8	23.0 - 26.0	34.22 - 38.68	6.276 - 6.366	159.41 - 161.70	6.023	153.0
G10-049-0720	7"	177.8	17.0 - 20.0	25.29 - 29.76	6.456 - 6.538	163.98 - 166.07	6.266	159.2
G10-049-0750	7-5/8"	193.7	33.7 - 39.0	50.14 - 58.03	6.625 - 6.765	168.27 - 171.83	6.375	161.9
G10-049-0760	7-5/8"	193.7	24.0 - 29.7	35.71 - 44.19	6.875 - 7.025	174.62 - 178.43	6.625	168.3
G10-049-0850	8-5/8"	219.1	32.0 - 40.0	47.61 - 59.51	7.725 - 7.921	196.21 - 201.19	7.500	190.5
G10-049-0860	8-5/8"	219.1	24.0 - 28.0	35.71 - 41.66	8.017 - 8.097	203.63 - 205.66	7.781	197.6
G10-049-0950	9-5/8"	244.4	47.0 - 53.5	69.93 - 79.60	8.535 - 8.681	216.79 - 220.50	8.250	209.6
G10-049-0960	9-5/8"	244.4	32.3 - 43.5	48.06 - 64.73	8.755 - 9.001	222.38 - 228.63	8.500	215.9

G-WR Wireline Adapter Kit					
Product Number	Size		Maximum O.D.		Connection
	in.	mm	in.	mm	
G10-011-0450	4-1/2"	114.3	3.695	93.9	Baker-10
G10-011-0550	5-1/2"	139.7	4.500	114.3	Baker-20
G10-011-0700 *	7"	177.8	5.250	133.4	

* Utilized for 7" and above sizes

G-WR Retrieving Tool					
Product Number	Size		Maximum O.D.		Connection
	in.	mm	in.	mm	
G10-081-0450	4-1/2"	114.3	3.688	93.7	2-3/8" EUE
G10-081-0560	5-1/2"	139.7	4.370	111.0	2-7/8" EUE
G10-081-0700	7"	177.8	5.000	127.0	
G10-081-0760	7-5/8"	193.7	6.625	168.3	
G10-081-0850	8-5/8"	219.1	7.390	187.7	
G10-081-0950	9-5/8"	244.4	8.250	209.6	

